

Codi Oil



CLARK Oil Distributors, Inc. • 801 W. Dewey Ave. • P.O. Box 970 Sapulpa, OK. 74067 (918) 224-3070

Product Information Sheet

PIP-C120-98

CODI Synthetic ATF

DESCRIPTION:

CODI Synthetic ATF contains an advanced additive system along with specially selected mineral and synthetic base oils that provide service fill performance in a wide variety of automatic transmissions. It gives protection that meets or exceeds the industry's highest quality standards.

It includes most GM, Ford, Chrysler, Jeep, Saturn, Honda/Acura, Toyota, Nissan, Mitsubishi, Hyundai, Mercedes, BMW, VW/Audi and other transmissions. **Always check the owner's manual for details.**

CODI Synthetic ATF is a balanced field tested formulation that gives assurance of the best possible wear protection on gears and transmission parts for a longer life. Excellent friction and antishudder durability for smooth and consistent shifting. Improved low temperature operability, resistance to high temperature oxidation and thermal degradation along with corrosion and foam inhibitors for year around protection. In addition, good compatibility with seal material minimizes leaks. It contains a shear-stable polymer that minimizes oil viscosity change over a wide temperature range. All these performance features provide enhanced transmission performance and life.

APPLICATION:

CODI Synthetic ATF is suitable for use in applications where manufacturers recommend:

- Dex VI,III,II,Type A, Suffix A
- Mer V,SP,LV,138CJ,166H
- Chy +4,+3
- Asian and European Cars
- JASO 1A
- ZF
- Voith
- Allison C-4/C-3

Not suitable for use in CVT (continuously variable transmissions), Ford Type F, and Allison TES-295

FEATURES & BENEFITS:





Multi-Vehicle Capability: Formulated to meet the stringent wear, friction, and operational requirements of most automatic transmissions for a smooth driving experience.

Wear Protection: The highest level of wear protection for gears and internal moving parts allowing for maximum transmission life.

Friction Retention: Uniquely balanced frictional properties provide anti-shudder durability, smooth shifting and precise lock-up throughout the service interval.

High Temperature Protection: Excellent oxidation and thermal protection that reduces sludge, varnish, and deposits for longer life.

Cold Temperature Operability: Improved cold temperature flow characteristics assures ease of pumping, quick start up and smooth shifting, even at extremely low temperatures.



CODI Synthetic ATF
Typical Properties

Qualifications:	Synthetic ATF
Viscosity, cSt	
@ 40°C	32.9
@ 100°C	7.2
Viscosity Index	195
Brookfield @ -40 cP	9000
API Gravity	33.1
Pour Point, °F	-58
Flash Point, °F	385

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

HEALTH & SAFETY:

A complete material safety data sheet is available upon request. Used oil may be harmful. Avoid prolonged or repeated skin contact. Wash clothing and exposed areas with soap and water. Don't pollute - return used oil to a collection center.