

Codi Oil



CLARK Oil Distributors, Inc. • 801 W. Dewey Ave. • P.O. Box 970 Sapulpa, OK. 74067 (918) 224-3070

Product Information Sheet

PIP-C120-98

CODI Type-F ATF

DESCRIPTION:

CODI Type-F Automatic Transmission Fluid (ATF) meets the performance requirements for special frictional characteristics, transmission cleanliness, and low temperature pumpability required in the Ford Type F specification.

Type-F is formulated with high quality base oils and a special additive system designed to permit rapid power transfer during shift cycles. The special additive system also prevents wear, oil seal deterioration, excessive oxidation from high temperature operation and corrosion of copper containing alloys used in some transmissions.

The anti-wear performance of Type-F ATF has long been a desired characteristic for hydrostatic transmission performance and many hydraulic system manufacturers.

APPLICATION:

CODI Type-F ATF is recommended for use in the following applications:

- ¥ Ford M2C-33F or G
- ¥ Sundstrand Hydrostatic Transmissions
- ¥ Hydraulic systems as recommended by the manufacturer

Type F is NOT recommended for use where Dexron™, Dexron™ II, Dexron™ III, or Chrysler 7176 Fluids are required since excessive shudder may occur.





FEATURES & BENEFITS:

Frictional Properties: Stable frictional properties assure rapid power transfer and excellent retention of shifting performance throughout the service interval.

High Temperature Protection: Good protection for high operating temperatures experienced in vehicles and hydraulic systems.

Anti-wear Performance: Superior anti-wear performance leads to less wear and longer equipment life in transmissions and hydraulic systems.

Cold Flow: Good cold temperature flow characteristics assures ease of pumping and good shifting capabilities, even at low temperatures.



CODI Type-F ATF
Typical Properties

Qualifications:	Type-F ATF
Viscosity, cSt	
@ 40°C	36.5
@ 100°C	7.5
Viscosity Index	178
API Gravity	31.4
Pour Point, °F	<-40
Flash Point, °F	370

The typical properties listed reflect the general characteristics of the product, and are not manufacturing specifications. Normal batch-to-batch variations should be expected.

HEALTH & SAFETY:

A complete material safety data sheet is available upon request. Used oil may be harmful. Avoid prolonged or repeated skin contact. Wash clothing and exposed areas with soap and water. Don't pollute - return used oil to a collection center.